

TECHNICAL DATA SHEET

Construction Joints & Details



Krystol Waterstop Treatment™

Product Code: K-321

DESCRIPTION

Krystol Waterstop Treatment is a primary component of the Krystol® Waterstop System that is used to permanently waterproof concrete construction joints. It is a cementitious slurry applied to horizontal and vertical construction joints that provides additional crystalline growth that assists in waterproofing the structure, as well as provides a protection of rebar found in the jointing from corrosion. Specially formulated with Kryton's proven Krystol technology, the active ingredients in Krystol Waterstop Treatment combine chemically with water and un-hydrated cement to form millions of needle-shaped crystals that grow in all directions to fill any capillary pores, cracks and joints that might otherwise allow water to pass.



FEATURES & BENEFITS

- Easy to install
- Provides a permanent waterstop treatment as part of the Krystol Waterstop System
- Durable; resistant to rain and foot traffic once hardened
- Safe for contact with potable water; certified to NSF/ANSI Standard 61
- Easy to inspect; distinctive yellow color increases reliability and quality control

RECOMMENDED USES

Krystol Waterstop Treatment is used in conjunction with Krystol Waterstop Grout and/or Krytonite as part of the Krystol Waterstop System at all static concrete-to-concrete joints where water penetration is a concern. Krystol Waterstop Treatment can also be used by itself as a dampproofing treatment.

PROPERTIES

Physical Properties	
Appearance	Buff / yellow powder
Bulk density	1.2 g/cm ³ (75 lb. /cu. ft.)
pH (when mixed with water)	13
Plastic Properties	
Working time (20°C / 68°F, 50% RH)	35 minutes
Hardening time (20°C / 68°F, 50% RH)	2.5 Hours

APPLICATION

Refer to Krystol Waterstop Application Instruction 4.11 to 4.22 (as applicable) before using this product. Consult a Kryton Representative for help with selecting the appropriate joint detail.

Mix approximately 3 parts Krystol Waterstop Treatment to 1 part clean water (by volume) to a thick slurry consistency. Apply Treatment at construction joints prior to pouring next subsequent concrete. Protect from rain, rapid drying or freezing for at least 24 hours.

TECHNICAL DATA SHEET

Krystol Waterstop Treatment™

LIMITATIONS

Krystol Waterstop Treatment is effective for rigid structures only and may not reliably seal joints that experience variable loading or repeated movement. Consult a Kryton representative for project specific recommendations.

SAFETY

Read the Safety Data Sheet (SDS) for this product. For professional use only. This product becomes caustic when mixed with water or perspiration. Avoid contact with skin or eyes. Avoid breathing dust. Wear long sleeves, safety goggles and impervious gloves.

PACKAGING

Krystol Waterstop Treatment is available in 5 kg (11 lb.) and 25 kg (55 lb.) resealable pails

SHELF LIFE

Krystol Waterstop Treatment has a minimum shelf life of 24 months for unopened pails, and 4 months for properly resealed pails.

WARRANTY

Kryton International Inc. (Kryton) warrants that Kryton products are free from manufacturing defects and comply with the specifications given in their respective technical data sheet. Because conditions of use, such as site conditions, surface preparations, workmanship, concrete ingredients, weather, structural issues and other factors are beyond the control of Kryton, no warranty can be given as to the results of use. Purchaser agrees to seek the advice of qualified professionals and to determine for themselves the suitability of the products for their intended purpose and assumes all risks. Purchaser's sole remedy is limited to replacement of any product proven defective or at Kryton's option refund of the purchase price paid. THIS LIMITED WARRANTY CONTAINS THE ENTIRE OBLIGATION OF KRYTON. NO OTHER WARRANTIES, EXPRESS OR IMPLIED, SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. KRYTON SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. No representative of Kryton has the authority to make any representations or provision except as stated herein. Kryton reserves the right to change the properties of its products without notice.